

# STARTRAC

EU MODEL 263 **H**

**HYDROSTATIC  
TRANSMISSION**



**8G**  
THE EIGHTH  
GENERATION

Powered by



Note : Mid-Deck Mower is a Separate Implement.

MADE IN INDIA


EU-ENGLISH

# STARTRAC

EU MODEL 263-HST

**HYDROSTATIC TRANSMISSION**

Powered by






Also Available

**50+** Types of Matching Implements



	SPECIFICATIONS	STARTRAC 263 HST (Agricultural Tyres)	STARTRAC 263 HST (Turf Tyres)	STARTRAC 263 HST (Industrial/Flotation Tyres)	STARTRAC 263 HST (Agricultural Wide Tyres)	STARTRAC 263 HST (Galaxy Garden Pro Tyres)	STARTRAC 263 HST (Wider F-Agri Tyres)
Engine	Engine Horse Power Ps (kW)	25 (18.2)					
	Engine : Type	Mitsubishi Stage-V : Naturally Aspirated					
	No. of Cylinder	3					
	Capacity (CC)	1319					
	Rated Speed (RPM)	2500					
	Cooling System	Liquid Cooled					
	Bore / Stroke (mm)	78/92					
	Max Torque (Nm) @ RPM	76.3 (Nm) @ 2000 RPM					
Tyres	Front	180/85D12	23 x 8.5 - 12	23 x 8.5 - 12	6.5/80-12	220/55R12	23 x 8.5 - 12
	Rear	8.30 x 20	33 x 15.5 - 16.5	33 x 15.5 - 16.5	280/70R18	280/70R16	280/70R18
Transmission	Type	Hydrostatic					
	Gears	3 Forward, 3 Reverse (Options of High, Medium or Low Gear)					
	Speed (km / hr.)	0 to 22.02	0 to 20.61	0 to 21.30	0 to 21.00	0 to 19.60	0 to 21.00
	PTO RPM	Rear 540 @2406 ERPM / Mid 2000 @2430 ERPM					
	Steering	Hydrostatic Power Steering					
	Brake Type	Multi Disc Oil Immersed					
Hydraulic	Hydraulic System	Auto Draft Sensing & Depth Control (2 Levers)					
	Lift Capacity (kgs.)	750 (at Lower Link Point)					
	No. of Pumps	2 (One for Hydrostatic Steering & Unit, Other for Hydraulic System)					
	Auxiliary Hydraulics	1 DA Auxiliary Hydraulics with 2 QRCs (Optional Kit Available : Extra Secondary DA Auxiliary Hydraulics with 2 more QRCs)					
# Dimensions	Size LxWxH (mm)	2780* x 1140 x 2060	2780* x 1490 x 2040	2780* x 1490 x 2043	2780* x 1200 x 2040	2780* x 1260 x 2005	2780* x 1220 x 2040
	Wheel Base (mm)	1550	1550	1550	1550	1550	1550
	Rear Track Center (mm)	811 to 988	1080	1080	845 to 988	935	845 to 988
	Weight (kg)	1050	1092	1120	1052	1059	1056

\*Dimensions are with Standard Lower Links, it may vary with longer linkages.

#+/- 5% Tolerance variations

Note : Products undergo continuous upgradations. Hence, above mentioned specifications are subject to change without prior notice.