


STARTRAC

GLOBETRAC

50 HP Series



Powerful 3 Cylinder Engine



Collar Shift+Synchro Gear Box



Cost Efficient



Low Fuel Consumption



Powerful Hydraulic



Also Available : Matching Implements



STARTRAC 5036

GLOBETRAC 4WD

STARTRAC

Technical Specification

MODEL :
STARTRAC 5036 4WD - GLOBETRAC SERIES

ENGINE	Kirloskar
Model	3R 1040
Power (HP)	50 Hp
Type	4 Stroke Water Cooled Diesel Engine
No. of Cylinder	3
Bore/Stroke (cm)	105/120
Cubic Capacity	3117
Rated Engine Speed	2200
Torque	188 Nm / 20% Backup Torque
Air Cleaner	Dry Air Cleaner With Clogging Sensor
CLUTCH	
Type	Dual Clutch
Plate Size	280 mm (Primary)
TRANSMISSION	Carraro
Type	Collar Shift + Synchro FWD REV
Gears	8F + 8R
Speed	Min 2.95 Km/hr, Max 33.44 Km/hr
PTO	
Type	Live PTO (ADDC) with Reverse PTO
PTO Speed	540 & 540E
PTO Options	Live PTO
No. of Splines	6
BRAKES	
Brakes	Oil Immersed Disc Brakes
Parking Brake	Independent
STEERING	
Steering Type	Hydrostatic Power Steering
HYDRAULICS	
Hyd. Pump Type	TANDEM PUMP
A. Position	To Hold The Lower Link At Any Desired Height
B. Automatic Depth Draft Control	Maintains Uniform Draft
C. Mix Control	For Simultaneous Use of Position And Draft Control For Optimum Field Output.
Lifting Capacity (Kg)	1500
Auxiliary Hydraulics	Optional : 1 DA with 2 QRCs
3 Point Linkage	CAT-1 & CAT-2



Standard supply
Front Weight with Platform,
ROPS, & Sun Roof Canopy

ELECTRICAL INSTRUMENTS	
Battery , Capacity	88 Ah
Alternator	12V, 36A
Starter Motor	12V, 2.3 kW
TYRES	
Front	8.3x20
Rear	14.9x28
FUEL TANK	
Capacity	55 Ltr.
DIMENSIONS	
Front Track Width	1320 mm
Rear Track Width	1420 mm
Tractor Length	3800 mm
Tractor Width	1728 mm
Min. Ground Clearance	435 mm
Min. Turning Radius	R-7.1 m, L-7.1 m
Weight of Tractor with Ballast Weight	2395 Kg
P.T.O. No. of Splines	6

Note : All Specifications are subject to change without prior notice. GLOBETRAC series is available only for exports.

Also Available in **2WD**