


STARTRAC

GLOBETRAC

60 HP Series



Powerful 4 Cylinder Engine



Synchromesh Gear Box



Cost Efficient



Low Fuel Consumption



Powerful Hydraulic



Also Available : Matching Implements



STARTRAC 6036

GLOBETRAC 4WD



Technical Specification

MODEL :
STARTRAC 6036 4WD - GLOBETRAC SERIES

ENGINE	Kirloskar
Model	4R 1040
Power (HP)	60 Hp
Type	4 Stroke Water Cooled Diesel Engine
No. of Cylinder	4
Bore/Stroke (cm)	105/120
Cubic Capacity	4160
Rated Engine Speed	2200
Torque	227 Nm / 18.2% Backup Torque
Air Cleaner	Dry Air Cleaner With Clogging Sensor
CLUTCH	
Type	Dual Clutch
Plate Size	280 mm (Primary)
TRANSMISSION	Carraro
Type	Synchromesh, with H/L/M Collar Shift
Gears	12F + 12R
Speed	Min 1.49 Km/hr, Max 30.82 Km/hr
PTO	
Type	Independent, Ground PTO, Multi speed
PTO Speed	540 & 540E
PTO Options	Live PTO, Ground PTO, Multi speed
No. of Splines	6
BRAKES	
Brakes	Oil Immersed Disc Brakes
Parking Brake	Independent
STEERING	
Steering Type	Hydrostatic Power Steering
HYDRAULICS	
Hyd. Pump Type	TANDEM PUMP
A. Position	To Hold The Lower Link At Any Desired Height
B. Automatic Depth Draft Control	Maintains Uniform Draft
C. Mix Control	For Simultaneous Use of Position And Draft Control For Optimum Field Output.
Lifting Capacity (Kg)	2200
Auxiliary Hydraulics	1 DA with 2 QRCs
3 Point Linkage	CAT-2



Standard supply
Front Weight with Platform, Rear Wheel Weight,
ROPS, & Sun Roof Canopy

ELECTRICAL INSTRUMENTS	
Battery , Capacity	100 Ah
Alternator	12V, 36A
Starter Motor	12V, 2.7 kW
TYRES	
Front	9.5x24
Rear	16.9x28
FUEL TANK	
Capacity	65 Ltr.
DIMENSIONS	
Front Track Width	1525 mm
Rear Track Width	1465 mm
Tractor Length	4100 mm
Tractor Width	1905 mm
Min. Ground Clearance	420 mm
Min. Turning Radius	R-8.2 m, L-8.3 m
Weight of Tractor with Ballast Weight	3050 Kg
P.T.O. No. of Splines	6

Note : All Specifications are subject to change without prior notice. GLOBETRAC series is available only for exports.

Also Available in **2WD**