


# STARTRAC

## GLOBETRAC

### 75 HP Series



Powerful 4 Cylinder Engine



Synchromesh Gear Box



Cost Efficient



Low Fuel Consumption



Powerful Hydraulic



### Also Available : Matching Implements



# STARTRAC 7536

## GLOBETRAC 4WD



## Technical Specification

MODEL :  
STARTRAC 7536 4WD - GLOBETRAC SERIES

ENGINE	
Model	Kirloskar 4R 1040
Power (HP)	72 Hp
Type	4 Stroke Water Cooled Diesel Engine
No. of Cylinder	4
Bore/Stroke (cm)	105/120
Cubic Capacity	4160
Rated Engine Speed	2200
Torque	295 Nm / 18% Backup Torque
Air Cleaner	Dry Air Cleaner With Clogging Sensor
CLUTCH	
Type	Dual Clutch
Plate Size	310 mm (Primary)
TRANSMISSION	
Type	Carraro Synchronesh, with H/L/M Collar Shift
Gears	12F + 12R
Speed	Min 1.53 Km/hr, Max 31.47 Km/hr
PTO	
Type	Independent, Ground PTO, Multi speed
PTO Speed	540 & 540E
PTO Options	Live PTO, Ground PTO, Multi speed
No. of Splines	6
BRAKES	
Brakes	Oil Immersed Disc Brakes
Parking Brake	Independent
STEERING	
Steering Type	Hydrostatic Power Steering
HYDRAULICS	
Hyd. Pump Type	TANDEM PUMP
A. Position	To Hold The Lower Link At Any Desired Height
B. Automatic Depth Draft Control	Maintains Uniform Draft
C. Mix Control	For Simultaneous Use of Position And Draft Control For Optimum Field Output.
Lifting Capacity (Kg)	2500
Auxiliary Hydraulics	2 DA with 4 QRCs
3 Point Linkage	CAT-2



Standard supply  
Front Weight with Platform, Rear Wheel Weight,  
ROPS, & Sun Roof Canopy

ELECTRICAL INSTRUMENTS	
Battery , Capacity	100 Ah
Alternator	12V, 36A
Starter Motor	12V, 2.7 kW
TYRES	
Front	11.2x24
Rear	16.9x30
FUEL TANK	
Capacity	80 Ltr.
DIMENSIONS	
Front Track Center	1506 mm
Rear Track Center	1535 mm
Tractor Length	4235 mm
Tractor Width	1970 mm
Min. Ground Clearance	445 mm
Min. Turning Radius	R-11.3 m, L-11.6 m
Weight of Tractor with Ballast Weight	3315 Kg
P.T.O. No. of Splines	6

Note : All Specifications are subject to change without prior notice. GLOBETRAC series is available only for exports.

Also Available in **2WD**