

STARTRAC

22

Your **STAR** Performer



Powered by
MITSUBISHI
DIESEL ENGINE

www.startractors.com

STAGE V

ENGINE

Engine Horse Power Ps (kW)	21.5 (15.8)
Engine Type	Mitsubishi L3E - Stage - V
No. of Cylinder	3
Capacity (CC)	953
Rated Speed (RPM)	3000
Cooling System	Liquid Cooled
Bore / Stroke (mm)	76/70
Max Torque (Nm) @ RPM	52 (Nm) @ 2000 RPM

TRANSMISSION

Type	Mechanical Sliding Mesh Transmission : Side Shift Gear Levers
Gears	9 Forward, 3 Reverse
PTO RPM	540 & 540 E
Steering	Hydrostatic Power Steering
Brake Type	Multi Disc Oil Immersed

HYDRAULIC

Hydraulic System	Auto Draft Sensing & Depth Control (2 Levers)
Lift Capacity (kgs.)	850 (at Lower Link Point)
No. of Pumps	1 (for Steering & Hydraulic System with Priority Valve)
Auxiliary Hydraulics	Trailer Hyd, Tipping Single Outlet Standard <small>(Optional Kits Available : 1 DA Auxiliary Hydraulics with 2 QRCs OR 2 DA Auxiliary Hydraulics with 4 QRCs)</small>

KEY FEATURES



Next Generation Styling



Hydrostatic Power Steering



Engine : Stage V Mitsubishi 3 Cylinder



9+3 Gears Side Shift Levers



Front Opening Bonnet



Differential Lock



Ergonomic Seating & Footboard Area



Powerful 850 kg Hyd. Lifting Capacity



TYRE OPTIONS	Agriculture	Turf	Industrial (Flotation)	Agricultural Wide Plus	Agrimax Turf RT 333 Garden	Wider F - Agri	Industrial (Regular)	Basic Agri	Agriculture Wide
Front	180/85D12	23 x 8.5 - 12	23 x 8.5 - 12	180/85D12	240/60R12	23 x 8.5 - 12	23 x 8.5 - 12	5.00 x 12	6.5/80-12
Rear	8.30 x 20	33 x 15.5 - 16.5	33 x 15.5 - 16.5	280/70R20	320/65R18	280/70R18	12 x 16.5	8.00 x 18	280/70R18

SPEED & DIMENSIONS*

	Agriculture	Turf	Industrial (Flotation)	Agricultural Wide Plus	Agrimax Turf RT 333 Garden	Wider F - Agri	Industrial (Regular)	Basic Agri	Agriculture Wide
Max. Speed (km/hr)	23.61	21.70	22.47	23.53	22.54	22.16	22.37	21.49	22.16
Size L x W x H (mm)	2700* x 1080 x 2100	2700* x 1390 x 2050	2700* x 1390 x 2050	2700* x 1167 x 2095	2700* x 1220 x 2080	2700* x 1220 x 2060	2700* x 1264 x 2050	2700* x 1050 x 2060	2700* x 1200 x 2060
Wheel Base (mm)	1490	1490	1490	1490	1490	1490	1490	1490	1490
Rear Track Center (mm)	811 to 988	980 to 1080	980 to 1080	883	883 to 988	845 to 988	939	743 to 988	845 to 988
Weight (kg)	900	942	970	931	931	906	944	879	902

*Dimensions are with Standard Lower Links, it may vary with longer linkages.

#+/- 5% Tolerance variations

Note : Products undergo continuous upgradations. Hence, above mentioned specifications are subject to change without prior notice.