

STARTRAC

26

Your **STAR** Performer



Powered by



www.startractors.com

STAGE V

STARTRAC 26

EU HOMOLOGATED TRACTOR MODEL

STAGE V

STYLE
COMFORT
VERSATILITY

ENGINE

Engine Horse Power Ps (kW)	25 (18.2)
Engine Type	Mitsubishi MVS3L2 - Stage - V
No. of Cylinder	3
Capacity (CC)	1319
Rated Speed (RPM)	2500
Cooling System	Liquid Cooled
Bore / Stroke (mm)	78/92
Max Torque (Nm) @ RPM	76.3 (Nm) @ 2000 RPM

TRANSMISSION

Type	Sliding Mesh Transmission : Side Shift Gear Levers
Gears	9 Forward, 3 Reverse
PTO RPM	540 & 540 E
Steering	Hydrostatic Power Steering
Brake Type	Multi Disc Oil Immersed


HYDRAULIC

Hydraulic System	Auto Draft Sensing & Depth Control (2 Levers)
Lift Capacity (kgs.)	850 (at Lower Link Point)
No. of Pumps	2 (One for Hydrostatic Steering & Other for Hydraulic System)
Auxiliary Hydraulics	1 DA Auxiliary Hydraulics with 2 QRCs

KEY FEATURES



Next Generation Styling



Hydrostatic Power Steering



Engine : Stage V Mitsubishi 3 Cylinders



9+3 Gears Side Shift Levers



Front Opening Bonnet



Differential Lock



Ergonomic Seating & Footboard Area



Powerful 850 kg Hyd. Lifting Capacity



Powered by
MITSUBISHI DIESEL ENGINE



Agriculture



Turf



Industrial (Flotation)



Agricultural Wide Plus



Agrimax Turf RT 333 Garden



Wider F - Agri



Industrial (Regular)



Basic Agri

TYRE OPTIONS

Front	180/85D12	23 x 8.5 - 12	23 x 8.5 - 12	180/85D12	240/60R12	23 x 8.5 - 12	23 x 8.5 - 12	5.00 x 12
Rear	8.30 x 20	33 x 15.5 - 16.5	33 x 15.5 - 16.5	280/70R20	320/65R18	280/70R18	12 x 16.5	8.00 x 18

SPEED & DIMENSIONS#

Max. Speed Rounded Off (km/hr)	20	18	19	20	19	18	19	18
Size L x W x H (mm)	2700* x 1080 x 2100	2700* x 1390 x 2050	2700* x 1390 x 2050	2700* x 1167 x 2095	2700* x 1220 x 2080	2700* x 1220 x 2060	2700* x 1264 x 2050	2700* x 1050 x 2060
Wheel Base (mm)	1490	1490	1490	1490	1490	1490	1490	1490
Rear Track Center (mm)	811 to 988	980 to 1080	980 to 1080	883	883 to 988	845 to 988	939	743 to 988
Weight (kg)	950	992	1020	981	981	956	994	929

*Dimensions are with Standard Lower Links, it may vary with longer linkages.

#+/- 5% Tolerance variations

Note : Products undergo continuous upgradations. Hence, above mentioned specifications are subject to change without prior notice.